

Product information

Speed Petrol Additive

PI 28/03/13/2024



Description

Ash-free, self-mixing combination of active agents. Characterized by its outstanding cleaning and material protection properties.

Properties

- for carburetor and fuel-injection engines
- reduces residue
- normalizes gasoline consumption and exhaust emissions
- highly economical
- reduces the risk of knocking combustion
- prevents the build-up of deposits
- keeps the fuel system clean
- tested for turbochargers and catalytic converters
- increases operational reliability
- good corrosion protection



and may be considered reliable, although not legally binding.

Technical data

Base	additive mixture in liquid carrier
Color / appearance	light yellow, clear
Regulation on Flammable Liquids Class (Germany)	A II
Flash point	> 61 °C
Pour point	-45 °C
Form	liquid
Odor	characteristic
Viscosity at 40 °C	<7 mm ² /s
Density at 15 °C	0,7989 g/ml

Areas of application

For all 2-stroke and 4-stroke gasoline engines in the automotive sector as well as the shipping and industrial sector. Also suitable for the preservation of engines during long periods of non-use.

Application

Contents (1 l) sufficient for 400 l of gasoline. One measuring cup (25 ml integrated in the cap) is sufficient for 10 l of fuel. The product mixes with the fuel automatically. For long-term application with every refueling.

Available pack sizes

1 l Can sheet metal	5105
	D
195 l Black plate barrel	4054
	GB

Our information is based on thorough research